

and operation.

# PREVENTATIVE MAINTENANCE CHECKLIST ELECTRIC PEGASUS SERIES

The service intervals for the Preventative Maintenance Checklist are base on normal operating conditions. The normal operating conditions include eight hours a day, or forty hours a week. If operating conditions or duty cycles are more severe, servicing of trucks should be preformed more frequently.

E	SERIAL #	MODEL_		HOUR M	ETER REAL	DING
onnected /r	be preformed during t emoved and the mach d then repair any item	ine turned off.	The scope	of the Pre	eventative N	
	TOPIC		DAILY OR 8 HOURS	MONTHLY OR 200 HOURS	6 MONTHS OR 1200 HOURS	ANNUALLY
	on Checklist (To be Com	pleted by				
Inspect & cle longer readab	ean I.D. tags for readability ble or are missing from true	ck.	Х			
	sis & cab structures for phervisor if damage is found		х			
Inspect mirro	ors and windows ( if equipp	ed).	Х			
	utton on steering wheel to		x			
	e light(s) for proper working	condition	Х			
	robe light(s) for proper working		X			
	eadlights (front/rear) for pro		X			
	-up alarm(s) for proper wor	king condition	Х			
	for wear and adjust to prop		X			
Inspect seat condition.	belt for wear and proper or	perating	х			
Test seat sw	itch (deadman) for proper o	peration.	Х			
inspect all ga	auges for proper working fu	nctions.	Х			
nspect all sv	witches for proper working Lights, Fan, Etc)		Х			
(Lift, Lower, S	draulic levers for proper w Side Shift, Fork Position, E	tc)	Х			
(Accelerator			x			
	ery disconnect switch for p	roper operation.	X			
	rails (if equipped).		Х			
	s and floor of cab for clean	iness.	Х			
	EER WHEELS:					
	ny physical wear or damag k torque of lug nuts on hub		x			
HYDRAULIC:						
Check hydrai	ulic fluid level. Maintain lev fied "FULL" mark.	el of hydraulic	х			
Inspect hose	s and piping for leaks at a or cracked hoses, loose fit		х			
	draulic cylinders for moun	ting, leakage,	x			



# PREVENTATIVE MAINTENANCE CHECKLIST ELECTRIC PEGASUS SERIES

TOPIC	DAILY OR 8 HOURS	MONTHLY OR 200 HOURS	6 MONTHS OR 1200 HOURS	ANNUALLY
MAST ASSEMBLY:				
Check all mast mounting hardware.	Х			
Inpsect for missing or broken pins and links.	Х			
CARRIAGE ASSEMBLY:				
Inspect forks.	Х			
BRAKES:	•			
Check for leaks.	Х			
PARKING BRAKE:	•	,		
Manually adjust the brake lever / cable for proper actuation.	Х			
SAFETY:				
Report any other dangerous or hazordous conditions found prior to operation to your foreman / supervisor / manager immediately.	х			

Below is the Preventative Maintenance Checklist that needs to be conducted by either the Maintenance Department of your company or a Maintenance Technician from the dealer that this truck was purchased from. The scope of this checklist is to inspect and then repair any items not meeting acceptable standards.

TOPIC	DAILY OR 8 HOURS	MONTHLY OR 200 HOURS	6 MONTHS OR 1200 HOURS	ANNUALLY
Drive Axle				
Visually inspect daily.				
Check mounting bolts / lug nuts.			Х	
Maintain oil levels in differential and planetary hubs.		Х		
maintenace and type of lubrication. (Section B).				Х
Drive Shaft				
Lubricate drive shafts, universal joints, slip joints.		Х		
Check attaching bolts.			Х	
Steer Axle				
Visually inspect daily.				
Lubricate all grease fittings.		Х		
Lubricate wheel bearings and spindles.				Х
Check mounting bolts.			Х	
Inspect steer rings / stops.			Х	
Check axle caps for tightness and if any are missing.		Х		
Check cylinder for proper operation and leaks.		X		
Lubricate central lube block.		Х		



# PREVENTATIVE MAINTENANCE CHECKLIST ELECTRIC PEGASUS SERIES

Brakes  Check fluid level in wet disc type brakes. Check for wear in mechanical brakes. X Check fluid level in wet disc type brakes. X Check fluid level in wet disc type brakes. X Check fluid level in wet disc type brakes. X Check fluid level in wet disc type brakes. X Check fluid level in wet disc type brakes. X Check fluid level in wet disc type brakes. X Check fluid level in wet disc type brakes. X Check fluid level in wet disc type brakes. X Check fluid level in wet disc type brakes. X Check fluid level in wet disc type brakes. X Check fluid level in wet fluid fl			MONTHLY	6 MONTHS		
Brakes Check fluid level in wet disc type brakes. Check for wear in mechanical brakes. Check for wear in mechanical brakes. X Refer to brake maintenance section. (Section B) Accumulator - Precharge to be 800-1000 psi. Operation cycle should get 4 to 6 brake pedal compressions before pump recharges accumulator. (See Hyd. Section).  Parking Brake Brake pads (replace when required). Actuator adjustment. (initial adjustment required when parking brake pads are replaced.)  Mast Assembly Visually inspect daily. Lubricate rast pivot bushings. Lubricate initer and outer mast channels. (as required). Actuator adjustment and outer mast channels. (as required). Lubricate and clean chains. Check for wear. Check all mast mounting hardware.  Carriage Assembly Visually inspect daily. Lubricate and clean rollers. Lubricate and clean rollers. Lubricate only fins and wear pads. Inspect and clean rollers. Lubricate cylinder mountings, grease fittings, special attachments.  Hydraulic System Inspect hydraulic pump(s) for leakage and operation. Drain and clean inside of tank. After flushing the entire hydraulic system, refill tank.  Hydraulic Filters Clean breathers.  X Clean breathers. X Clean	TOPIC	_			ΔΝΝΙΙΔΙ Ι Υ	
Brakes Check fluid level in wet disc type brakes. Check for wear in mechanical brakes. X Check for wear in mechanical brakes. X Refer to brake maintenance section. (Section B) Accumulator - Precharge to be 800-1000 psi. Operation cycle should get 4 to 6 brake pedal compressions before pump recharges accumulator. (See Hyd. Section).  Parking Brake Brake pads (replace when required). Actuator adjustment. (initial adjustment required when parking brake pads are replaced.)  Mast Assembly Visually inspect daily. Lubricate mast pixel bushings. Lubricate inner and outer mast channels. (as required).  Lubricate inner and outer mast channels. (as a x Lubricate inner and outer mast channels. (as required).  Lubricate inner and outer mast channels. (as x Lubricate fork pins and wear pads. Inspect and clean rollers. Lubricate cylinder mountings, grease fittings, special x At altachments.  Hydraulic System Inspect daily. Lubricate cylinder mountings, grease fittings, special attachments.  X Inspect and clean inside of tank. After flushing the entire hydraulic system, refill tank.  X Clean breathers.  Clean / replace tank strainer(s).  X Clean breathers.  X Change hydraulic oil filter(s) / element(s)  X Change hydraulic oil filter(s) / element(s)  X Clean breathers.  X Clean of inkages not having greaseable  X	16116	8 HOURS			ANNOALLI	
Check fluid level in wet disc type brakes. Check for wear in mechanical brakes. Check for wear in mechanical brakes. Check for wear in mechanical brakes. X Refer to brake maintenance section. (Section B) Accumulator - Precharge to be 800-1000 psi. Operation cycle should get 4 to 6 brake pedal compressions before pump recharges accumulator. (See Hyd. Section).  Parking Brake Brake pads (replace when required). Actuator adjustment. (initial adjustment required when parking brake pads are replaced.)  Mast Assembly Visually inspect daily. Lubricate mast pivot bushings. Lubricate into cylinder bushings, grease fittings. X Lubricate into rand outer mast channels. (as required). Lubricate and clean chains. Check for wear. Check all mast mounting hardware.  Carriage Assembly Visually inspect daily. Lubricate and clean chains. Check for wear. X Check all mast mounting hardware.  X Carriage Assembly Visually inspect daily. Lubricate for the pins and wear pads. Inspect and clean rollers. Lubricate cylinder mountings, grease fittings, special attachments.  Hydraulic System Inspect hydraulic pump(s) for leakage and operation. Drain and clean inside of tank. After flushing the entire hydraulic system, refill tank.  Hydraulic Filters Clean / replace tank strainer(s). Clean breathers. Change hydraulic oil filter(s) / element(s). For further maintenance of hydraulic valve refer to Section H.  Misc. Lubricate all grease fittings not listed elsewhere in manual. Use oil on linkages not having greaseable			Поско	ПООКО		
Check fluid level in wet disc type brakes. Check for wear in mechanical brakes. Check for wear in mechanical brakes. Check for wear in mechanical brakes. X Refer to brake maintenance section. (Section B) Accumulator - Precharge to be 800-1000 psi. Operation cycle should get 4 to 6 brake pedal compressions before pump recharges accumulator. (See Hyd. Section).  Parking Brake Brake pads (replace when required). Actuator adjustment. (initial adjustment required when parking brake pads are replaced.)  Mast Assembly Visually inspect daily. Lubricate mast pivot bushings. Lubricate into cylinder bushings, grease fittings. X Lubricate into rand outer mast channels. (as required). Lubricate and clean chains. Check for wear. Check all mast mounting hardware.  Carriage Assembly Visually inspect daily. Lubricate and clean chains. Check for wear. X Check all mast mounting hardware.  X Carriage Assembly Visually inspect daily. Lubricate for the pins and wear pads. Inspect and clean rollers. Lubricate cylinder mountings, grease fittings, special attachments.  Hydraulic System Inspect hydraulic pump(s) for leakage and operation. Drain and clean inside of tank. After flushing the entire hydraulic system, refill tank.  Hydraulic Filters Clean / replace tank strainer(s). Clean breathers. Change hydraulic oil filter(s) / element(s). For further maintenance of hydraulic valve refer to Section H.  Misc. Lubricate all grease fittings not listed elsewhere in manual. Use oil on linkages not having greaseable	Brakes	=	=	=		
Check for wear in mechanical brakes.  Refer to brake maintenance section. (Section B)  Accumulator. Precharge to be 800-1000 psi. Operation cycle should get 4 to 6 brake pedal compressions before pump recharges accumulator. (See Hyd. Section).  Parking Brake  Brake pads (replace when required). Actuator adjustment. (initial adjustment required when parking brake pads are replaced.)  Mast Assembly  Visually inspect daily. Lubricate mast pivot bushings. Lubricate tilt cylinder bushings, grease fittings.  Lubricate inner and outer mast channels. (as required). Lubricate and clean chains. Check for wear.  Check all mast mounting hardware.   Carriage Assembly  Visually inspect daily. Lubricate fork pins and wear pads. Inspect and clean rollers. Lubricate of pilore mountings, grease fittings, special attachments.  Hydraulic System Inspect hydraulic pump(s) for leakage and operation.  Drain and clean inside of tank. After flushing the entire hydraulic system, refill tank.  Hydraulic Filters  Clean / replace tank strainer(s). Clean breathers. Change hydraulic oil filter(s) / element(s). For further maintenance of hydraulic valve refer to Section H.  Misc.  Lubricate all grease fittings not listed elsewhere in manual. Use oil on linkages not having greaseable  X  X  X  X  X  X  X  X  X  X  X  X  X			Y			
Refer to brake maintenance section. (Section B)  Accumulator - Precharge to be 800-1000 psi. Operation cycle should get 4 to 6 brake pedal compressions before pump recharges accumulator. (See Hyd. Section).  Parking Brake  Brake pads (replace when required).  Actuator adjustment. (initial adjustment required when parking brake pads are replaced.)  Mast Assembly  Visually inspect daily.  Lubricate mast pivot bushings.  Lubricate ill cylinder bushings, grease fittings.  Lubricate inner and outer mast channels. (as required).  Lubricate and clean chains. Check for wear.  Check all mast mounting hardware.   Carriage Assembly  Visually inspect daily.  Lubricate fork pins and wear pads. Inspect and clean rollers.  Lubricate fork pins and wear pads. Inspect and clean rollers.  Lubricate cylinder mountings, grease fittings, special attachments.  Hydraulic System  Inspect and clean inside of tank. After flushing the entire hydraulic system, refill tank.  Hydraulic Filters  Clean replace tank strainer(s).  Clean prelace tank strainer(s).  Clean prelace tank strainer(s).  Clean prelace tank strainer(s).  Clean prevalue in time and prevalue refer to Section H.  Misc.  Lubricate all grease fittings not listed elsewhere in manual. Use oil on linkages not having greaseable  X						
Accumulator - Precharge to be 800-1000 psi. Operation cycle should get 4 to 6 brake pedal compressions before pump recharges accumulator. (See Hyd. Section).  Parking Brake Brake pads (replace when required). Actuator adjustment. (initial adjustment required when parking brake pads are replaced.)  Mast Assembly Visually inspect daily. Lubricate mast pivot bushings. Lubricate mast pivot bushings. Lubricate inter and outer mast channels. (as required). Lubricate inner and outer mast channels. (as required). Lubricate and clean chains. Check for wear. Check all mast mounting hardware.  Carriage Assembly Visually inspect daily. Lubricate fork pins and wear pads. Inspect and clean rollers. Lubricate of the pins and wear pads. Lubricate cylinder mountings, grease fittings, special attachments.  Hydraulic System Inspect hydraulic pump(s) for leakage and operation. Drain and clean inspect tank. After flushing the entire hydraulic system, refill tank.  Hydraulic Filters Clean / replace tank strainer(s). Clean breathers. Change hydraulic oil filter(s) / element(s).  Kisc. Lubricate on linkages not having greaseable  X  Misc. Lubricate on linkages not having greaseable			^		v	
Operation cycle should get 4 to 6 brake pedal compressions before pump recharges accumulator. (See Hyd. Section).    Parking Brake	, ,				^	
compressions before pump recharges accumulator. (See Hyd. Section).  Parking Brake Brake pads (replace when required). Actuator adjustment. (initial adjustment required when parking brake pads are replaced.)  Mast Assembly  Visually inspect daily. Lubricate mast pivot bushings. Lubricate mast pivot bushings. Lubricate inner and outer mast channels. (as required). Lubricate and clean chains. Check for wear.  Check all mast mounting hardware.  Carriage Assembly  Visually inspect daily. Lubricate fork pins and wear pads. Inspect and clean rollers. Lubricate cylinder mountings, grease fittings, special attachments.  Whydraulic System Inspect hydraulic pump(s) for leakage and operation. Drain and clean inside of tank. After flushing the entire hydraulic system, refill tank.  Phydraulic Filters  Clean / replace tank strainer(s). Clean breathers.  Change hydraulic oil filter(s) / element(s). For further maintenance of hydraulic valve refer to Section H.  Misc. Lubricate oil on linkages not having greaseable  X   X  Actuator adjustment required when park and parking required when parking parki						
See Hyd. Section :   Parking Brake				Х		
Parking Brake Brake pads (replace when required). Actuator adjustment. (initial adjustment required when parking brake pads are replaced.)  Mast Assembly Visually inspect daily. Lubricate mast pivot bushings. Lubricate tilt cylinder bushings, grease fittings. X Lubricate inner and outer mast channels. (as required). Lubricate and clean chains. Check for wear. Check all mast mounting hardware.  Carriage Assembly Visually inspect daily. Lubricate fork pins and wear pads. Inspect and clean rollers. Lubricate office prountings, grease fittings, special attachments.  Hydraulic System Inspect hydraulic pump(s) for leakage and operation. Drain and clean inside of tank. After flushing the entire hydraulic system, refill tank.  Hydraulic Filters Clean / replace tank strainer(s). Clean breathers.  X  Misc. Lubricate all grease fittings not listed elsewhere in manual. Use oil on linkages not having greaseable  X  Misc. Lubricate all grease fittings not listed elsewhere in manual. Use oil on linkages not having greaseable						
Brake pads (replace when required).  Actuator adjustment. (initial adjustment required when parking brake pads are replaced.)  Mast Assembly  Visually inspect daily.  Lubricate mast pivot bushings.  Lubricate litt cylinder bushings, grease fittings.  Lubricate inner and outer mast channels. (as required).  Lubricate and clean chains. Check for wear.  Check all mast mounting hardware.   Carriage Assembly  Visually inspect daily.  Lubricate and clean chains. Check for wear.  X  Check all mast mounting hardware.   Carriage Assembly  Visually inspect daily.  Lubricate fork pins and wear pads.  Inspect and clean rollers.  Lubricate cylinder mountings, grease fittings, special attachments.  Hydraulic System  Inspect hydraulic pump(s) for leakage and operation.  Drain and clean inside of tank. After flushing the entire hydraulic system, refill tank.  Hydraulic Filters  Clean / replace tank strainer(s).  Clean / replace tank strainer(s).  Clean phydraulic oil filter(s) / element(s)  For further maintenance of hydraulic valve refer to Section H.  Misc.  Lubricate all grease fittings not listed elsewhere in manual. Use oil on linkages not having greaseable	(See Hyd. Section).					
Brake pads (replace when required).  Actuator adjustment. (initial adjustment required when parking brake pads are replaced.)  Mast Assembly  Visually inspect daily.  Lubricate mast pivot bushings.  Lubricate litt cylinder bushings, grease fittings.  Lubricate inner and outer mast channels. (as required).  Lubricate and clean chains. Check for wear.  Check all mast mounting hardware.   Carriage Assembly  Visually inspect daily.  Lubricate and clean chains. Check for wear.  X  Check all mast mounting hardware.   Carriage Assembly  Visually inspect daily.  Lubricate fork pins and wear pads.  Inspect and clean rollers.  Lubricate cylinder mountings, grease fittings, special attachments.  Hydraulic System  Inspect hydraulic pump(s) for leakage and operation.  Drain and clean inside of tank. After flushing the entire hydraulic system, refill tank.  Hydraulic Filters  Clean / replace tank strainer(s).  Clean / replace tank strainer(s).  Clean phydraulic oil filter(s) / element(s)  For further maintenance of hydraulic valve refer to Section H.  Misc.  Lubricate all grease fittings not listed elsewhere in manual. Use oil on linkages not having greaseable	Parking Prako	:	:	:		
Actuator adjustment. (initial adjustment required when parking brake pads are replaced.)  Mast Assembly  Visually inspect daily.  Lubricate mast pivot bushings.  Lubricate tilt cylinder bushings, grease fittings.  Lubricate inner and outer mast channels. (as required).  Lubricate and clean chains. Check for wear.  Check all mast mounting hardware.   Carriage Assembly  Visually inspect daily.  Lubricate fork pins and wear pads.  Inspect and clean rollers.  Lubricate cylinder mountings, grease fittings, special attachments.  Hydraulic System  Inspect hydraulic pump(s) for leakage and operation.  Drain and clean inside of tank. After flushing the entire hydraulic system, refill tank.  Hydraulic Filters  Clean / replace tank strainer(s).  Clean breathers.  Change hydraulic of hydraulic valve refer to Section H.  Misc.  Lubricate all grease fittings not listed elsewhere in manual. Use oil on linkages not having greaseable  X				Y		
parking brake pads are replaced.)  Mast Assembly  Visually inspect daily.  Lubricate mast pivot bushings.  Lubricate inner and outer mast channels. (as required).  Lubricate and clean chains. Check for wear.  Check all mast mounting hardware.   Carriage Assembly  Visually inspect daily.  Lubricate fork pins and wear pads.  Inspect and clean rollers.  Lubricate cylinder mountings, grease fittings, special attachments.  Whydraulic System  Inspect hydraulic pump(s) for leakage and operation.  Drain and clean inside of tank. After flushing the entire hydraulic system, refill tank.  Hydraulic Filters  Clean / replace tank strainer(s).  Clean breathers.  Change hydraulic oil filter(s) / element(s)  For further maintenance of hydraulic valve refer to Section H.  Misc.  Lubricate all grease fittings not listed elsewhere in manual. Use oil on linkages not having greaseable						
Mast Assembly  Visually inspect daily.  Lubricate mast pivot bushings.  Lubricate inner and outer mast channels. (as required).  Lubricate and clean chains. Check for wear.  Check all mast mounting hardware.   Carriage Assembly  Visually inspect daily.  Lubricate fork pins and wear pads.  Inspect and clean rollers.  Inspect and clean rollers.  Inspect and clean rollers.  Inspect and clean rollers.  Whydraulic System  Inspect hydraulic pump(s) for leakage and operation.  Drain and clean inside of tank. After flushing the entire hydraulic system, refill tank.  Hydraulic Filters  Clean / replace tank strainer(s).  Clean breathers.  Clean product ifficers  X  Change hydraulic oil filter(s) / element(s).  For further maintenance of hydraulic valve refer to Section H.  Misc.  Lubricate all grease fittings not listed elsewhere in manual. Use oil on linkages not having greaseable	, , , , , , , , , , , , , , , , , , , ,			Х		
Visually inspect daily.  Lubricate mast pivot bushings.  Lubricate inner and outer mast channels. (as required).  Lubricate and clean chains. Check for wear.  Check all mast mounting hardware.   Carriage Assembly  Visually inspect daily.  Lubricate fork pins and wear pads.  Inspect and clean rollers.  Lubricate cylinder mountings, grease fittings, special attachments.   Hydraulic System  Inspect hydraulic pump(s) for leakage and operation.  Drain and clean inside of tank. After flushing the entire hydraulic system, refill tank.  Hydraulic Filters  Clean / replace tank strainer(s).  Clean breathers.  Change hydraulic oil filter(s) / element(s)  For further maintenance of hydraulic valve refer to Section H.  Misc.  Lubricate all grease fittings not listed elsewhere in manual. Use oil on linkages not having greaseable	parking brake pads are replaced.)		<u> </u>			
Visually inspect daily.  Lubricate mast pivot bushings.  Lubricate inner and outer mast channels. (as required).  Lubricate and clean chains. Check for wear.  Check all mast mounting hardware.   Carriage Assembly  Visually inspect daily.  Lubricate fork pins and wear pads.  Inspect and clean rollers.  Lubricate cylinder mountings, grease fittings, special attachments.   Hydraulic System  Inspect hydraulic pump(s) for leakage and operation.  Drain and clean inside of tank. After flushing the entire hydraulic system, refill tank.  Hydraulic Filters  Clean / replace tank strainer(s).  Clean breathers.  Change hydraulic oil filter(s) / element(s)  For further maintenance of hydraulic valve refer to Section H.  Misc.  Lubricate all grease fittings not listed elsewhere in manual. Use oil on linkages not having greaseable	Mast Assembly	-	-	-		
Lubricate mast pivot bushings.  Lubricate tilt cylinder bushings, grease fittings.  Lubricate inner and outer mast channels. (as required).  Lubricate and clean chains. Check for wear.  Check all mast mounting hardware.   Carriage Assembly  Visually inspect daily.  Lubricate fork pins and wear pads.  Inspect and clean rollers.  Lubricate cylinder mountings, grease fittings, special attachments.  Hydraulic System  Inspect hydraulic pump(s) for leakage and operation.  Drain and clean inside of tank. After flushing the entire hydraulic system, refill tank.  Hydraulic Filters  Clean / replace tank strainer(s).  Clean breathers.  Change hydraulic oil filter(s) / element(s)  For further maintenance of hydraulic valve refer to Section H.  Misc.  Lubricate all grease fittings not listed elsewhere in manual. Use oil on linkages not having greaseable	-					
Lubricate inner and outer mast channels. (as required).  Lubricate inner and outer mast channels. (as required).  Lubricate and clean chains. Check for wear.  Check all mast mounting hardware.   Carriage Assembly  Visually inspect daily.  Lubricate fork pins and wear pads.  Inspect and clean rollers.  Lubricate cylinder mountings, grease fittings, special attachments.  Hydraulic System  Inspect hydraulic pump(s) for leakage and operation.  Drain and clean inside of tank. After flushing the entire hydraulic system, refill tank.  Hydraulic Filters  Clean / replace tank strainer(s).  Clean breathers.  Clean breathers.  Change hydraulic oil filter(s) / element(s)  For further maintenance of hydraulic valve refer to Section H.  Misc.  Lubricate all grease fittings not listed elsewhere in manual. Use oil on linkages not having greaseable			Y			
Lubricate inner and outer mast channels. (as required).  Lubricate and clean chains. Check for wear.  Check all mast mounting hardware.  Carriage Assembly  Visually inspect daily.  Lubricate fork pins and wear pads.  Inspect and clean rollers.  Lubricate cylinder mountings, grease fittings, special attachments.  Hydraulic System  Inspect hydraulic pump(s) for leakage and operation.  Drain and clean inside of tank. After flushing the entire hydraulic system, refill tank.  Hydraulic Filters  Clean / replace tank strainer(s).  Clean breathers.  Change hydraulic oil filter(s) / element(s)  For further maintenance of hydraulic valve refer to Section H.  Misc.  Lubricate all grease fittings not listed elsewhere in manual. Use oil on linkages not having greaseable						
required).  Lubricate and clean chains. Check for wear.  Check all mast mounting hardware.   Carriage Assembly  Visually inspect daily.  Lubricate fork pins and wear pads.  Inspect and clean rollers.  Lubricate cylinder mountings, grease fittings, special attachments.  Hydraulic System  Inspect hydraulic pump(s) for leakage and operation.  Drain and clean inside of tank. After flushing the entire hydraulic system, refill tank.  Hydraulic Filters  Clean / replace tank strainer(s).  Clean breathers.  Change hydraulic oil filter(s) / element(s)  For further maintenance of hydraulic valve refer to Section H.  Misc.  Lubricate all grease fittings not listed elsewhere in manual. Use oil on linkages not having greaseable  X			^			
Lubricate and clean chains. Check for wear.  Check all mast mounting hardware.  X  Carriage Assembly  Visually inspect daily.  Lubricate fork pins and wear pads.  Inspect and clean rollers.  Lubricate cylinder mountings, grease fittings, special attachments.  Hydraulic System  Inspect hydraulic pump(s) for leakage and operation.  Drain and clean inside of tank. After flushing the entire hydraulic system, refill tank.  Hydraulic Filters  Clean / replace tank strainer(s).  Clean breathers.  Change hydraulic oil filter(s) / element(s)  For further maintenance of hydraulic valve refer to Section H.  Misc.  Lubricate all grease fittings not listed elsewhere in manual. Use oil on linkages not having greaseable			Х			
Carriage Assembly  Visually inspect daily.  Lubricate fork pins and wear pads.  Inspect and clean rollers.  Lubricate cylinder mountings, grease fittings, special attachments.  Hydraulic System  Inspect hydraulic pump(s) for leakage and operation.  Drain and clean inside of tank. After flushing the entire hydraulic system, refill tank.  Hydraulic Filters  Clean / replace tank strainer(s).  Clean breathers.  Change hydraulic oil filter(s) / element(s)  For further maintenance of hydraulic valve refer to Section H.  Misc.  Lubricate all grease fittings not listed elsewhere in manual. Use oil on linkages not having greaseable  X	1 /		v			
Carriage Assembly  Visually inspect daily.  Lubricate fork pins and wear pads.  Inspect and clean rollers.  Lubricate cylinder mountings, grease fittings, special attachments.  Hydraulic System  Inspect hydraulic pump(s) for leakage and operation.  Drain and clean inside of tank. After flushing the entire hydraulic system, refill tank.  Hydraulic Filters  Clean / replace tank strainer(s).  Clean breathers.  Change hydraulic oil filter(s) / element(s)  For further maintenance of hydraulic valve refer to Section H.  Misc.  Lubricate all grease fittings not listed elsewhere in manual. Use oil on linkages not having greaseable  X						
Visually inspect daily.  Lubricate fork pins and wear pads.  Inspect and clean rollers.  Lubricate cylinder mountings, grease fittings, special attachments.  Hydraulic System Inspect hydraulic pump(s) for leakage and operation.  Drain and clean inside of tank. After flushing the entire hydraulic system, refill tank.  Hydraulic Filters  Clean / replace tank strainer(s).  Clean breathers.  Change hydraulic oil filter(s) / element(s)  For further maintenance of hydraulic valve refer to Section H.  Misc.  Lubricate all grease fittings not listed elsewhere in manual. Use oil on linkages not having greaseable  X   X  X  X  X  X  X  X  X  X  X  X	Check all mast mounting hardware.	<u> </u>	^	<u> </u>		
Visually inspect daily.  Lubricate fork pins and wear pads.  Inspect and clean rollers.  Lubricate cylinder mountings, grease fittings, special attachments.  Hydraulic System Inspect hydraulic pump(s) for leakage and operation.  Drain and clean inside of tank. After flushing the entire hydraulic system, refill tank.  Hydraulic Filters  Clean / replace tank strainer(s).  Clean breathers.  Change hydraulic oil filter(s) / element(s)  For further maintenance of hydraulic valve refer to Section H.  Misc.  Lubricate all grease fittings not listed elsewhere in manual. Use oil on linkages not having greaseable  X   X  X  X  X  X  X  X  X  X  X  X	Carriage Assembly					
Lubricate fork pins and wear pads.  Inspect and clean rollers.  Lubricate cylinder mountings, grease fittings, special attachments.  Hydraulic System  Inspect hydraulic pump(s) for leakage and operation.  Drain and clean inside of tank. After flushing the entire hydraulic system, refill tank.  Hydraulic Filters  Clean / replace tank strainer(s).  Clean breathers.  Change hydraulic oil filter(s) / element(s)  For further maintenance of hydraulic valve refer to Section H.  Misc.  Lubricate all grease fittings not listed elsewhere in manual. Use oil on linkages not having greaseable  X  X  X  X  X  X  X  X  X  X  X  X  X						
Inspect and clean rollers.  Lubricate cylinder mountings, grease fittings, special attachments.  Hydraulic System  Inspect hydraulic pump(s) for leakage and operation.  Drain and clean inside of tank. After flushing the entire hydraulic system, refill tank.  Hydraulic Filters  Clean / replace tank strainer(s).  Clean breathers.  Change hydraulic oil filter(s) / element(s)  For further maintenance of hydraulic valve refer to Section H.  Misc.  Lubricate all grease fittings not listed elsewhere in manual. Use oil on linkages not having greaseable  X  X  X  X  X  X  X  X  X  X  X  X  X			х			
Lubricate cylinder mountings, grease fittings, special attachments.  Hydraulic System Inspect hydraulic pump(s) for leakage and operation.  Drain and clean inside of tank. After flushing the entire hydraulic system, refill tank.  Hydraulic Filters  Clean / replace tank strainer(s).  Clean breathers.  Change hydraulic oil filter(s) / element(s)  For further maintenance of hydraulic valve refer to Section H.  Misc.  Lubricate all grease fittings not listed elsewhere in manual. Use oil on linkages not having greaseable  X  Inspect hydraulic X  X  X  X  X  Inspect hydraulic pump(s) for leakage and operation.  X  X  X  X  X  Inspect hydraulic pump(s) for leakage and operation.  X  X  X  Inspect hydraulic pump(s) for leakage and operation.  X  X  Inspect hydraulic pump(s) for leakage and operation.  X  X  Inspect hydraulic pump(s) for leakage and operation.  X  X  Inspect hydraulic pump(s) for leakage and operation.  X  X  Inspect hydraulic pump(s) for leakage and operation.  X  X  Inspect hydraulic pump(s) for leakage and operation.  X  X						
Hydraulic System Inspect hydraulic pump(s) for leakage and operation.  Drain and clean inside of tank. After flushing the entire hydraulic system, refill tank.  Hydraulic Filters  Clean / replace tank strainer(s).  Clean breathers.  Change hydraulic oil filter(s) / element(s)  For further maintenance of hydraulic valve refer to Section H.  Misc.  Lubricate all grease fittings not listed elsewhere in manual. Use oil on linkages not having greaseable  X  Inspect hydraulic pump(s) for leakage and operation.  X  X  X  X  X  Inspect hydraulic pump(s) for leakage and operation.  X  X  X  Inspect hydraulic pump(s) for leakage and operation.  X  X  Inspect hydraulic pump(s) for leakage and operation.  X  X  Inspect hydraulic pump(s) for leakage and operation.  X						
Hydraulic System Inspect hydraulic pump(s) for leakage and operation.  Drain and clean inside of tank. After flushing the entire hydraulic system, refill tank.  Hydraulic Filters  Clean / replace tank strainer(s).  Clean breathers.  Change hydraulic oil filter(s) / element(s)  For further maintenance of hydraulic valve refer to Section H.  Misc.  Lubricate all grease fittings not listed elsewhere in manual. Use oil on linkages not having greaseable  X   X  X  X  X  X  X  X  X  X  X  X	, , , , , , , , , , , , , , , , , , , ,		X			
Inspect hydraulic pump(s) for leakage and operation.  Drain and clean inside of tank. After flushing the entire hydraulic system, refill tank.    Hydraulic Filters	attaonmenter	!	!	!		
Inspect hydraulic pump(s) for leakage and operation.  Drain and clean inside of tank. After flushing the entire hydraulic system, refill tank.    Hydraulic Filters	Hvdraulic Svstem					
Drain and clean inside of tank. After flushing the entire hydraulic system, refill tank.  Hydraulic Filters  Clean / replace tank strainer(s).  Clean breathers.  Change hydraulic oil filter(s) / element(s)  For further maintenance of hydraulic valve refer to Section H.  Misc.  Lubricate all grease fittings not listed elsewhere in manual. Use oil on linkages not having greaseable  X			Х			
hydraulic system, refill tank.  Hydraulic Filters  Clean / replace tank strainer(s).  Clean breathers.  Change hydraulic oil filter(s) / element(s)  For further maintenance of hydraulic valve refer to Section H.   Misc.  Lubricate all grease fittings not listed elsewhere in manual. Use oil on linkages not having greaseable  X					.,	
Hydraulic Filters  Clean / replace tank strainer(s).  Clean breathers.  Change hydraulic oil filter(s) / element(s)  For further maintenance of hydraulic valve refer to Section H.  Misc.  Lubricate all grease fittings not listed elsewhere in manual. Use oil on linkages not having greaseable  X	_				X	
Clean / replace tank strainer(s).  Clean breathers.  Change hydraulic oil filter(s) / element(s)  For further maintenance of hydraulic valve refer to Section H.   Misc.  Lubricate all grease fittings not listed elsewhere in manual. Use oil on linkages not having greaseable  X	,					
Clean breathers.  Change hydraulic oil filter(s) / element(s)  For further maintenance of hydraulic valve refer to Section H.   Misc.  Lubricate all grease fittings not listed elsewhere in manual. Use oil on linkages not having greaseable  X	Hydraulic Filters					
Clean breathers.  Change hydraulic oil filter(s) / element(s)  For further maintenance of hydraulic valve refer to Section H.   Misc.  Lubricate all grease fittings not listed elsewhere in manual. Use oil on linkages not having greaseable  X	Clean / replace tank strainer(s).			Х		
Change hydraulic oil filter(s) / element(s)  For further maintenance of hydraulic valve refer to Section H.  Misc.  Lubricate all grease fittings not listed elsewhere in manual. Use oil on linkages not having greaseable  X				Х		
For further maintenance of hydraulic valve refer to Section H.  Misc.  Lubricate all grease fittings not listed elsewhere in manual. Use oil on linkages not having greaseable  X	Change hydraulic oil filter(s) / element(s)					
Misc.  Lubricate all grease fittings not listed elsewhere in manual. Use oil on linkages not having greaseable  X						
Lubricate all grease fittings not listed elsewhere in manual. Use oil on linkages not having greaseable					^	
Lubricate all grease fittings not listed elsewhere in manual. Use oil on linkages not having greaseable						
manual. Use oil on linkages not having greaseable						
	Lubricate all grease fittings not listed elsewhere in					
fittings.	manual. Use oil on linkages not having greaseable			Х		
	fittings.					



# PREVENTATIVE MAINTENANCE CHECKLIST ELECTRIC PEGASUS SERIES

TOPIC	DAILY OR 8 HOURS	MONTHLY OR 200 HOURS	6 MONTHS OR 1200 HOURS	ANNUALLY	
-------	---------------------	----------------------------	------------------------------	----------	--

Electrical System			
		Х	
Inspect all motors for proper operation.		^	
Inspect motor commutators / armatures. Replace as		Х	
required.			
Check motor mounting and electrical connectors.		Х	
Inspect all motor brushes and brush spring tension.		Х	
Check for excessive battery leakage to chassis.		Х	
Inspect battery connectors.	Х	·	
Inspect battery(s) for damage, corrosion, and leaks.	Х		
Inspect battery electrolyte level and specific gravity.			
(add water as required.)	Х		
Inspect battery tray for physical damage / corrosion.		Χ	
Inspect cables and connections for tightness.		Х	
Inspect battery cables for corrosion.	Х		
Refer to Battery Requirements in manual for further			
maintenance on battery.		Х	
Inspect F/R switch assembly for proper operation.	Х		
Check wiring and terminals (keep clean and bright).		Χ	
Inspect tips of contactors for overheating or burning.		·	
Replace tips as needed. (F/R, Main, Lift, Power			
Steering, Field Weakening, Etc).		Χ	
Check hourmeter for proper operation. (If applicable).	Х		

### \*\*\*ATTENTION\*\*\*

Before performing any of the procedures on the Preventative Maintenance Checklist, Safety should be your primary concern. Remember to abide by all safety practices established by your company. If you notice any unsafe or hazardous conditions before starting any procedure, report it to your foreman / supervisor / manager immediately.

Revised: 02-29-08